

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name: Van Iperen CalMag Zinc Horticultural Grade

The solid mixture of calcium nitrate with small amounts of zinc nitrate, ammonium nitrate, and water.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture: as fertilizer. Uses advised against – not identified.

1.3. Details of the supplier of the safety data sheet

Van Iperen International BV Smidsweg 24 3273 LK Westmaas - Nederland T +31 (0) 186 578 888 - F +31 (0) 186 573 452 info@iperen.com - www.vaniperen.com

1.4. Emergency telephone number

Country	Official advisory body	Address	Emergency number
Ireland (Republic of)	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964
United Kingdom	Guy's & St Thomas' Poisons Unit Medical Toxicology Unit, Guy's & St Thomas' Hospital Trust	Avonley Road SE14 5ER London	0870 243 2241

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation 1272/2008 (CLP)

Acute Tox. 4, H302: Harmful if swallowed. Eye Dem. 1, H318: Causes serious eye damage

2.2. Labelling in accordance with Regulation 1272/2008 (CLP)

Signal word: Danger Hazard pictogram: GHS07 GHS05



Hazard statements:

H302: Harmful if swallowed.

H318: Causes serious eye damage.

Precautionary statements:

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product

P301+312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing

P330: Rinse mouth

P310: Immediately call a POISON CENTER or doctor/physician.

P501: Dispose content/containers to an authorized waste facility.

2.3. Other hazards

The mixture does not meet the criteria for PBT or vPvB in accordance with Annex XIII of the REACH Regulation. (see section 12).

SECTION 3: Composition/information on ingredients

3.1. Substances - not concern

3.2. Mixtures

Hazard substances:

Substance	Concentration	CAS No	13446-18-9
Magnesium nitrate hexahydrate		EC No	233-826-7
		Index No	Not available
		REACH No	01-2119491164-38-xxxx
		Classification according to Regulation	Not classified



		1272/2008	
		CAS No	10124-37-5
		EC No	233-332-1
Calcium nitrate	50-53 % w/w	Index No	Not available
Calcium mirate	30-33 % W/W	REACH No	01-2119495093-35-xxxx
		Classification according to Regulation	Acute Tox 4, H302 Eye Dem.
		1272/2008	1, H318
		CAS No	6484-52-2
		EC No	229-347-8
Ammonium nitrate	1,7-2,9 % w/w	Index No	Not available
Ammonium muate	1,7-2,9 70 W/W	REACH No	01-2119490981-27-xxxx
		Classification according to Regulation	Ox. Solid H272 Eye Irrit. 2,
		1272/2008	H319
		CAS No	666748-59-0
		EC No	931-053-6
ZnIDHA	1,6-2,0 % w/w	Index No	Not available
ZIIIDIIA	1,0-2,0 /0 W/W	REACH No	01-2119446084-43-xxxx
		Classification according to Regulation	Not classidied
		1272/2008	Not classicied
		CAS No	666828-79-1
		EC No	938-868-6
CuIDHA	0,17-0,27 % w/w	Index No	Not available
	0,17-0,27 % W/W	REACH No	01-2120011103-83-xxxx
		Classification according to Regulation	Acute Tox 4, H302 Aquatic
		1272/2008	Chronic 3, H412

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice : The first step is to put the injured person from a contaminated environment.

If swallowed:

- 1. Rinse mouth, give 2-3 glasses of water to drink. Never give anything by mouth to an unconscious person.
- 2. Seek medical attention.

In case of eye contact:

- 1. Immediately flush eyes with large amounts of water for at least 15 minutes while holding the eyelids open to ensure that the entire surface is flushed.
- 2. Seek medical attention.

In case of skin contact:

- 1. Rinse off with plenty of water. Remove contaminated cloths.
- 2. If symptoms persist, seek medical attention.

If inhaled:

- 1. Unlikely route of exposure due to the form of the product solid.
- 2. Move to fresh air. If needed, seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Causes irritation to eyes and digestive system (if swallowed) and skin.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment: Symptomatic treatment.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Use water only! Contact professional fire-fighters immediately. For small fires, do NOT use chemicals, carbon dioxide, halon or foams. For large fires flood fire with water from a distance.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition / combustion products: produces oxides of nitrogen on combustion: NyOx.

Protective equipment:

High temperatures may cause pressure build-up in closed containers.

according to Regulation (EC) No. 453/2010



CalMag Zinc Horticultural Grade

During the thermal decomposition produced of harmful compounds.

Reduce dust and vapour with water spray. Brown fumes containing toxic nitrogen oxides

Explosive mixture: Not applicable-non-explosive.

5.3. Advice for firefighters

As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Clothing resistant to high temperatures.

Independent self-contained breathing apparatus.

SECTION 6: Accidental release measures

General advice: Do not flush into public water courses. Do not empty into drains, ground or surface water and soil. If the product enters drains or water, immediately inform appropriate authorities.

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment (section 8).

Avoid contact with eyes.

Do not let this chemical enter the environment.

Do not ingest.

6.2. Environmental precautions

Do not let product enter drains. If the product enters drains or water, immediately inform appropriate authorities.

6.3. Methods and material for containment and cleaning up

Use appropriate tools to put the spilled solid in a convenient waste disposal container. If necessary:

Collect up the product and place it in a sealable container. Suitably labeled.

Transfer carefully to container.

Then take the spare containers to an area reserved for subsequent recycling or disposal.

Do not put the cast down material back into the original container, for re-use.

Avoid prolonged or repeated exposure.

6.4. Reference to other sections

For disposal see section 13.

For personal protective equipment see section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep in original containers in a covered warehouse.

Storage in dry area.

Protect from direct sunlight.

7.2. Conditions for safe storage, including any incompatibilities

Keep away from incompatibles such as reducing agents, flammable agents, strong acids

Keep away from foodstuffs, beverages and feed.

Keep away from heat and sources of ignition.

7.3. Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Regulated occupational exposure limit values: none

Recommended occupational, consumer and environmental exposure limit values for main ingredient – calcium nitrate (following from the performed CSA):



Exposure pattern	Derived No Effect Level (DNEL)	
	Workers	General population
Oral1	Not applicable	8,33 mg/kg bw/d
Dermal1	15,013,9 mg/kg bw/day	8,33 mg/kg bw/day
Inhalation1	98 mg/m³	29 mg/m
	Predicted No Effect Level (PNEC) ²	
Aqua-freshwater	0.45 mg/l	
Aqua-marine water	0.045 mg/l	
Aqua-intermittent release	4.5 mg/l	
STP	18 mg/l	

^{1:} As the substance is classified for acute oral toxicity an acute DNEL should be derived for the general population. However, peak exposure is considered not possible and therefore an acute DNEL systemic will not be derived. Therefore, the long-term DNEL is considered sufficient to ensure that effects from acute oral exposure to the substance do not occur. As an dermal and inhalation acute toxicity hazard leading to Classification and Labelling of the substance has not been identified, the long-term DNEL is considered sufficient to ensure that effects from acute exposure to the substance do not occur (in accordance with ECHA Guidance on information requirements and chemical safety assessment: Chapter R.8: Characterisation of dose [concentration]-response for human health, May 2008 and Part B: Hazard Assessment, Draft new chapter B.8 Scope of Exposure Assessment, March 2010).

8.2. Exposure controls

Personal protective equipment:

Eye/face protection : Use safety goggles

Skin/hands protection : The selected protective gloves have to satisfy the specifications of UE Directive 89-689- EEC and

standard EN 374 derived from it. Use work clothes and shoes.

Industrial hygiene : Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.

Avoid contact with eyes.

Engineering Controls: No engineering controls.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties
Appearance : Solid, flakes
Colour : Bluish
Odour : Specific
pH value 10 % (w/v) solution : 6 - 7

Melting point/freezing point : No data available Initial boiling point : No data available Flash point : No data available Evaporation rate : No data available Flammability (solid, gas) : Not flammable

Upper/lower flammability or explosive limits : Not applicable-non-combustible

Vapour pressure : <0.00001 Pa at 20°C Vapour density : No data available Relative/bulk density : No data available Solubility(ies) 220 g/100 g water Partition coefficient: n-octanol/water : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity : Not applicable (solid) Not explosive Explosive properties

Oxidizing properties : No oxidizing properties

9.2. Other information

No data.

SECTION 10: Stability and reactivity

- 10.1 Reactivity Reactive with strong reducing agents.
- 10.2 Chemical stability Under normal storage and use of the substance is chemically stable.
- 10.3 Possibility of hazardous reactions The mixture reacts with strong reducing agents

^{2:} PNECsediment/soil/oral are not derived as these are not applicable/not relevant.



- 10.4 Conditions to avoid Avoid contact with strong heat sources such as solar radiation and flames.
- 10.5 Incompatible materials Strong reducing agents.
- 10.6 Hazardous decomposition products Intensive heated to temperatures> 330 ° C followed by decomposition with emission of toxic gases (nitrogen oxides).

SECTION 11: Toxicological information

There no available toxicological studies for the mixture as such. The assessment was made on the basis of ownership of components of the mixture.

a) Acute toxicity: harmful if swallowed

ingestion: swallowing small amounts can cause headache, dizziness.

Swallowing large quantities can cause severe gastrointestinal disorders.

- b) Skin corrosion/irritation no irritating
 c) Serious eye damage/eye irritation Causes serious eye damage
- d) Respiratory or skin sensitization no skin or respiratory sensitization
- e) Germ cell mutagenicity no mutagenic
- f) Carcinogenicity no carcinogenic
- g) Reproductive toxicity The mixture is not a threat to fertility.
- h) Specific target organ toxicity (STOT) single exposure not harmful
- i) Specific target organ toxicity (STOT)- repeated exposure not harmful
- j) Aspiration hazard not applicable

Potential health effects- No data available.

Signs and Symptoms of Exposure- No data available.

ACUTE TOXICITY

	ACUTE TOXICITY	
	Calcium Nitrate	Amonium nitrate
Acute oral toxicity:	300 mg/kg bw < LD ₅₀ < 2000 mg/kg bw (OECD 423)	LD ₅₀ : 2950 mg/kg bw (OECD 401)
Acute dermal toxicity:	LD ₅₀ : > 2000 mg/kg bw	LD ₅₀ : > 5000 mg/kg bw (OECD 402)
Acute inhalation toxicity:	No data, low vapour pressure, no exposure	LC ₅₀ : > 88.8 mg/l (no guideline followed)
	LOCAL EFFECTS	
Skin irritation:	Not irritating (OECD 404)	Not irritating (OECD 404)
Eye irritation:	Irritating (OECD 405)	Irritating (OECD 405)
Skin sensitization:	Not sensitizing (OECD 429)	Not sensitizing (OECD 429, with magnesium nitrate, nitric acid ammonium calcium salt, sodium nitrate)
	OTHER	
Sub-acute toxicity:	Oral 28-day NOAEL ≥ 1000 mg/kg bw/day (OECD 422)	Oral 28-day NOAEL ≥ 1500 mg/kg bw/day (OECD 422, with potassium nitrate) Oral 52-week NOAEL = 256 mg/kg bw/day (OECD 453, with ammonium sulfate) Inhalation 2-weeks NOAEL ≥ 185 mg/m³ (OECD 412)
Mutagenicity:	Negative (OECD 471)	Negative (OECD 471, 473, with nitric acid ammonium calcium salt)
	Negative (OECD 473)	Negative (OECD 476, with potassium nitrate)
	Negative (OECD 476)	
Reproductive toxicity:	Oral 28-day NOAEL ≥ 1500 mg/kg bw/day (OECD 422)	Oral 28-day NOAEL ≥ 1500 mg/kg bw/day (OECD 422, with potassium nitrate)
Carcinogenicity:	No data	Not carcinogenic (OECD 453, with ammonium sulfate)

SECTION 12: Ecological information

12.1. Toxicity

There no available ecotoxicological studies for the mixture as such. The data were based on studies of similar substances.

	Calcium Nitrate	Amonium nitrate
Fish (short-term):	96-h LC ₅₀ : 1378 mg/l (OECD 203)	48-h LC ₅₀ : 447 mg/l (no guideline followed)
Fish (long-term):	No data	No data
Daphnia magna (short-term):	48-h EC ₅₀ : 490 mg/l	48-h EC ₅₀ : 490 mg/l (no guideline followed , with potassium nitrate)
Daphnia magna (long-term):	No data	No data
Algae:	10-d EC ₅₀ : > 1700 mg/l (seawater)	10-d EC ₅₀ : > 1700 mg/l (seawater, no guideline followed, performed with potassium nitrate)
Inhibition of microbial activity:	3-h EC ₅₀ : >1000 mg/l, NOEC: 180 mg/l (OECD 209)	3-h EC ₅₀ : >1000 mg/l, NOEC: 180 mg/ (COED 209, with sodium nitrate)



12.2 Persistence and degradability

Biodegradation:

Standard test is not applicable as the mixture is an inorganic. In addition, biodegradation of nitrate can occur under anaerobic conditions, both under natural conditions and as a controlled process in many wastewater treatment plants, resulting in degradation products like nitrite, oxide of nitrogen, nitrogen, or ammonia. Nitrate degradation is fastest in anaerobic conditions. In the anaerobic transformation of nitrate into N2, N2O and NH3, the biodegradation rate in wastewater plant at 20°C is 70 g N/kg dissolved solid/day.

Hydrolysis:

No hydrolysable group is present, will completely dissociate into ions.

12.3 Bioaccumulative potential

Octanol-water partition coefficient (Kow): Not relevant as the substance is inorganic, but considered to be low based on high water solubility)

Bioconcentration factor (BCF): Low potential for bioaccumulation (based on ingredients properties).

12.4 Mobility in soil

Adsorption coefficient:

Low potential for adsorption (based on ingredients properties).

12.5 Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No 1907/2006, no PBT and vPvB assessment has been conducted since mixture is inorganic.

12.6 Other adverse effects - no data available

SECTION 13: Disposal considerations

Packaging mast be disposed of in compliance with the country-specific regulations or mast be passed to a packaging return system.

Waste Removal: Apply as fertilizer or transfer for disposal.

Disposing of the packaging: Empty containers contain residue of material on the inner surfaces. Thoroughly

empty containers to be transmitted to authorized waste collector

Empty packaging completely.

Prevent pollution of surface waters.

Prohibition: Do not dispose of untreated packing with ordinary industrial wastes.

SECTION	l 14: Tr	ansport	infori	mation

14.1	UN number	Not applicable
14.2	UN proper shipping name	Not applicable
14.3	Transport hazard class(es)	Not applicable
14.4	Packing group	Not applicable
14.5	Environmental hazards	Not applicable
14.6	Special precautions for user	Not applicable
14.7	Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- 1. REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENTAND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC with amendments
- 2. COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)
- 3. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL
- 4. of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006; with amendments
- 5. European Agreement concerning the International Carriage of Dangerous Goods by Road
- 6. Regulation (EU) No 649/2012 Of The European Parliament and of The Council of 4 July 2012 concerning the export and import of hazardous chemicals.
- 7. Regulation (EC) No 850/2004 Of The European Parliament and of The Council Of 29 April 2004 On Persistent Organic Pollutants And Amending Directive 79/117/EEC.

according to Regulation (EC) No. 453/2010



CalMag Zinc Horticultural Grade

15.2. Chemical Safety Assessment

The chemical safety assessment was not carried out.

SECTION 16: Other information

Other information:

Classification of mixture was carried on based on ingredients of the mixture (Additivity formula)

Abbreviations:

Acute Tox 4 – acute toxicity category 4

Eye Dem 1 - Serious eye damage category 1

Ox. Solid – Oxidizing solid H272 - May intensify fire; oxidizer

Acuatic Chronic 3 – Hazard to aquatic organisms NOAEL: No Observed Adverse Effect Level NOEC: No observed effect concentration.

LD50: Lethal Dose 50%. The LD50 corresponds to the dose of a tested substance causing 50% lethality during a specified time interval.

LC50: Lethal Concentration 50%. The LC50 corresponds to the concentration of a tested substance causing 50% lethality during a specified time interval.

EC50: Effective Concentration 50%. The EC50 corresponds to the concentration of a tested substance causing 50% changes in response (e.g. on growth) during a specified time interval.

BCF: Bioconcentration factor

PBT: Persistent, bioaccumulative and toxic **vPvB:** Very Persistent and very Bioccumulative

Company disclaimer

The information provided in this safety data sheet is correct to the best of our knowledge, information, and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any proceed, unless specified in the text.

VAN IPEREN

CalMag Zinc Horticultural Grade

Use descriptors related to the life cycle stage SU: 1/9/10 PROC2/5/8a/8b/9 ERC1 PC 12: Fertilisers Name of contributing environmental scenario (1) and corresponding ERC List of names of contributing worker scenarios (2) and corresponding PROC PROC 2: Use in closed, continuous process with occasional controlle exposure PROC 5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) PROC Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non- dedicated facilities		(1) For calcium nitrate tion of fertilizer products
Name of contributing environmental scenario (1) and corresponding ERC List of names of contributing worker scenarios (2) and corresponding PROC List of names of contributing worker scenarios (2) and corresponding PROC PROC 2: Use in closed, continuous process with occasional controllic exposure PROC 5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) PRC Transfer of substance or preparation (charging/discharging) from/to vessels/alog containers at noi-dedicated facilities PROC 8b: Transfer of substance or preparation (charging/discharging) from/to vessels/alog containers at noi-dedicated facilities PROC 9: Transfer of substance or preparation (charging/discharging from/to vessels/alog containers at noi-dedicated facilities PROC 9: Transfer of substance or preparation into small containers (dedicated filling line, including welghing) 2.1 Contributing scenario (1) controlling environmental exposure Environmental release during manufacturing ERC1 An environmental assessment has not been performed as the substance does not meet the criteria for being classified as dangerous for environment. 2.2 Contributing scenario (2) controlling worker exposure for manufacturing of the substance. All Process Categories are covered by this contributing scenario as all Operational Conditions (OCs) and Risk Management Measures (RM are identical). PROCC/2/Sa/Ba/b/ Product related conditions, e.g., the concentration of the substance in a mixture, the physical state of that mixture (solid, liquid; if solid: level of dustiness), package design affecting exposure Product related conditions, e.g., the concentration of the substance in a mixture, the physical state of that mixture (solid, liquid; if solid: level of dustiness), package design affecting worker's exposure Product related conditions of use, e.g., be how parts by the part of the substance of the second of the	Use descriptors related to the life cycle stage	SU : 1/9/10
List of names of contributing worker scenarios (2) and corresponding PROC 3. Use in closed, continuous process with occasional controlle exposure PROC 5. Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) PROC 3. Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at one-decitated facilities PROC 8b. Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at one-decitated facilities PROC 9. Transfer of substance or preparation into small containers (dedicated filling line, including weighing) 2.1 Contributing scenario (1) controlling environmental exposure Environmental release during manufacturing ERC1 An environmental assessment has not been performed as the substance does not meet the criteria for being classified as dangerous for environment. 2.2 Contributing scenario (2) controlling worker exposure for manufacturing of the substance. All Process Categories are covered by this contributing scenario as all Operational Conditions (OCs) and Risk Management Measures (RM are identical. PROC2/5/88/8b/9 Product characteristic Product related conditions, e.g. the concentration of the substance in a mixture, the physical state of that mixture (solid, liquid; if solid: level of dustiness), package design affecting exposure Amounts used Announts used at a workplace (per task or per shift); note: sometimes this information is not needed for assessment of worker's exposure Frequency and duration of use/exposure Duration per task, ductivity (e.g., hours per shift) and frequency (e.g. single events or repeated) of exposure Other given operational conditions effecting workers exposure Other given operational conditions affecting workers exposure Other given operational conditions affecting workers exposure Other given operational conditions affecting workers exposure Technical conditions and measures at process level (source) to prevent release Process design		
List of names of contributing worker scenarios (2) and corresponding PROC PROC 2: Use in closed, continuous process with occasional controlle exposure PROC 5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) PROC Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non- dedicated facilities PROC 8: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC 9: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities (edicated failing line, including weighing) 2.1 Contributing scenario (1) controlling environmental exposure Environmental release during manufacturing ERC1 An environmental assessment has not been performed as the substance does not meet the criteria for being classified as dangerous for tenvironment. 2.2 Contributing scenario (2) controlling worker exposure for manufacturing of the substance. All Process Categories are covered by this contributing scenario as all Operational Conditions (OCs) and Risk Management Measures (RM are identical. PROC2/5/88/8b/9 Product related conditions, e.g., the concentration of the substance in a mixture, the physical state of that mixture (solid, liquid; if solid: level of dustiness), package design affecting exposure Amounts used at a workplace (per task or per shift); note: sometimes this information is not needed for assessment of worker's exposure Prequency and duration of use, e.g., body parts potentially exposed Duration per task/activity (e.g., hours per shift) and frequency (e.g., single events or repeated) of exposure Purtual conditions of use, e.g., body parts potentially exposed Not applicable Process design aiming to prevent releases and hence exposure of workers; workers exposure Process design aiming to prevent releases and hence exposure of workers; Not applicable Technical conditions and measures to c	Name of contributing environmental scenario (1) and	
2.1 Contributing scenario (1) controlling environmental exposure Environmental release during manufacturing ERCI An environmental assessment has not been performed as the substance does not meet the criteria for being classified as dangerous for renvironment. 2.2 Contributing scenario (2) controlling worker exposure for manufacturing of the substance. 2.3 Process Categories are covered by this contributing scenario as all Operational Conditions (OCs) and Risk Management Measures (RM are identical. 2.4 PROC2/5/8a/8b/9 2.5 Product characteristic 2.5 Product related conditions, e.g., the concentration of the substance in a mixture, the physical state of that mixture (solid, liquid; if solid: level of dustiness), package design affecting exposure 3. Amounts used at a workplace (per task or per shift); note: sometimes this information is not needed for assessment of worker's exposure 3. Frequency and duration of use/exposure 4. Duration per task/activity (e.g., hours per shift) and frequency (e.g. single events or repeated) of exposure 4. Human factors not influenced by risk management 4. Particular conditions of use, e.g. body parts potentially exposed 5. as a result of the nature of the activity 6. Other given operational conditions e.g. technology or process techniques determining the initial release of substance from process into workers environment; room volume, whether the work is carried out outdoors/indoors, process conditions related to temperature and pressure. 7. Technical conditions and measures at process level (source) to prevent release 7. Process design aiming to prevent releases and hence exposure of workers environment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) 7. Containment as appropriate 6. Containment as appropriate 7. Containment as appropriate	List of names of contributing worker scenarios (2) and corresponding PROC	PROC 5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact) PROC 8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non- dedicated facilities PROC 8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC 9: Transfer of substance or preparation into small containers
Environmental release during manufacturing ERC1 An environmental assessment has not been performed as the substance does not meet the criteria for being classified as dangerous for revironment. 2.2 Contributing scenario (2) controlling worker exposure for manufacturing of the substance. All Process Categories are covered by this contributing scenario as all Operational Conditions (OCs) and Risk Management Measures (RM are identical. PROC2/5/8a/8b/9 Product characteristic Product related conditions, e.g. the concentration of the substance in a mixture, the physical state of that mixture (solid, liquid; if solid: level of dustiness), package design affecting exposure Amounts used Amounts used Amounts used at a workplace (per task or per shift); note: sometimes this information is not needed for assessment of worker's exposure Frequency and duration of use/exposure Duration per task/activity (e.g. hours per shift) and frequency (e.g. single events or repeated) of exposure Human factors not influenced by risk management Particular conditions of use, e.g. body parts potentially exposed as a result of the nature of the activity Other given operational conditions affecting workers exposure Other given operational conditions: e.g. technology or process techniques determining the initial release of substance from process into workers environment; room volume, whether the work is carried out outdoors/indoors, process conditions enabled to temperature and pressure. Technical conditions and measures at process level (source) to prevent release Process design aiming to prevent releases and hence exposure of workers; exposure of workers; exposure of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure		(dedicated filling line, including weigning)
An environmental assessment has not been performed as the substance does not meet the criteria for being classified as dangerous for environment. 2.2. Contributing scenario (2) controlling worker exposure for manufacturing of the substance. All Process Categories are covered by this contributing scenario as all Operational Conditions (OCs) and Risk Management Measures (RM are identical. PROC2/5/8a/8b/9 Product characteristic Product related conditions, e.g., the concentration of the substance in a mixture, the physical state of that mixture (solid, liquid; if solid: level of dustiness), package design affecting exposure Amounts used Amounts used at a workplace (per task or per shift); note: sometimes this information is not needed for assessment of worker's exposure Frequency and duration of use/exposure Duration per task/activity (e.g. hours per shift) and frequency (e.g. single events or repeated) of exposure Human factors not influenced by risk management Particular conditions of use, e.g. body parts potentially exposed as a result of the nature of the activity Other given operational conditions affecting workers exposure Other given operational conditions affecting workers exposure Technical conditions and measures at process level (source) to prevent release Process design aiming to prevent releases and hence exposure of workers; this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure		
2.2 Contributing scenario (2) controlling worker exposure for manufacturing of the substance. All Process Categories are covered by this contributing scenario as all Operational Conditions (OCs) and Risk Management Measures (RM are identical. PROC2/5/8a/8b/9 Product related conditions, e.g. the concentration of the substance in a mixture, the physical state of that mixture (solid, liquid; if solid: level of dustiness), package design affecting exposure Amounts used Amounts used a workplace (per task or per shift); note: sometimes this information is not needed for assessment of worker's exposure Frequency and duration of use/exposure Duration per task/activity (e.g. hours per shift) and frequency (e.g. single events or repeated) of exposure Human factors not influenced by risk management Particular conditions of use, e.g. body parts potentially exposed as a result of the nature of the activity Other given operational conditions affecting workers exposure Other given operational conditions e.g. technology or process techniques determining the initial release of substance from process into workers environment; room volume, whether the work is carried out outdoors/indoors, process conditions related to temperature and pressure. Process design aiming to prevent releases and hence exposure of workers; this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards Process design afficting to prevent releases, dispersion and exposure Organisational measures to prevent //limit releases, dispersion and exposure	An environmental assessment has not been performed as the substa	rance does not meet the criteria for being classified as dangerous for the
All Process Categories are covered by this contributing scenario as all Operational Conditions (OCs) and Risk Management Measures (RM are identical. PROC2/5/8a/8b/9 Product characteristic Product related conditions, e.g. the concentration of the substance in a mixture, the physical state of that mixture (solid, liquid; if solid: level of dustiness), package design affecting exposure Amounts used Amounts used Amounts used at a workplace (per task or per shift); note: sometimes this information is not needed for assessment of worker's exposure Frequency and duration of use/exposure Duration per task/activity (e.g., hours per shift) and frequency (e.g. single events or repeated) of exposure Human factors not influenced by risk management Particular conditions of use, e.g. body parts potentially exposed as a result of the nature of the activity Other given operational conditions: e.g. technology or process techniques determining the initial release of substance from process into workers environment; room volume, whether the work is carried out outdoors/indoors, process conditions related to temperature and pressure. Process design aiming to prevent releases and hence exposure of workers; this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards Process design aiming to prevent releases and hence exposure of workers; this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards 1. Containment as appropriate effectiveness of measure Other given operational conditions and measures to prevent /limit releases, dispersion and exposure		ufacturing of the substance.
Product related conditions, e.g. the concentration of the substance in a mixture, the physical state of that mixture (solid, liquid; if solid: level of dustiness), package design affecting exposure Amounts used Amounts used at a workplace (per task or per shift); note: sometimes this information is not needed for assessment of worker's exposure Frequency and duration of use/exposure Duration per task/activity (e.g. hours per shift) and frequency (e.g. single events or repeated) of exposure Human factors not influenced by risk management Particular conditions of use, e.g. body parts potentially exposed as a result of the nature of the activity Other given operational conditions: e.g. technology or process techniques determining the initial release of substance from process into workers environment; room volume, whether the work is carried out outdoors/indoors, process conditions related to temperature and pressure. Technical conditions and measures at process level (source) to prevent release Process design aiming to prevent releases and hence exposure of workers; this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure	All Process Categories are covered by this contributing scenario as a are identical. PROC2/5/8a/8b/9	
mixture, the physical state of that mixture (solid, liquid; if solid: level of dustiness), package design affecting exposure Amounts used at a workplace (per task or per shift); note: sometimes this information is not needed for assessment of worker's exposure Frequency and duration of use/exposure Duration per task/activity (e.g. hours per shift) and frequency (e.g. single vents or repeated) of exposure Human factors not influenced by risk management Particular conditions of use, e.g. body parts potentially exposed as a result of the nature of the activity Other given operational conditions: e.g. technology or process techniques determining the initial release of substance from process into workers environment; room volume, whether the work is carried out outdoors/indoors, process conditions related to temperature and pressure. Technical conditions and measures at process level (source) to prevent releases Process design aiming to prevent releases and hence exposure of workers; this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify a Good standard of general ventilation of Genalisational measures to prevent /limit releases, dispersion and exposure		
Amounts used at a workplace (per task or per shift); note: sometimes this information is not needed for assessment of worker's exposure Frequency and duration of use/exposure Duration per task/activity (e.g. hours per shift) and frequency (e.g. single events or repeated) of exposure Human factors not influenced by risk management Particular conditions of use, e.g. body parts potentially exposed as a result of the nature of the activity Other given operational conditions affecting workers exposure Other given operational conditions: e.g. technology or process techniques determining the initial release of substance from process into workers environment; room volume, whether the work is carried out outdoors/indoors, process conditions related to temperature and pressure. Process design aiming to prevent releases and hence exposure of workers; this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure	mixture, the physical state of that mixture (solid, liquid; if solid: leve	
Amounts used at a workplace (per task or per shift); note: sometimes this information is not needed for assessment of worker's exposure Frequency and duration of use/exposure Duration per task/activity (e.g. hours per shift) and frequency (e.g. single events or repeated) of exposure Human factors not influenced by risk management Particular conditions of use, e.g. body parts potentially exposed as a result of the nature of the activity Other given operational conditions: e.g. technology or process techniques determining the initial release of substance from process into workers environment; room volume, whether the work is carried out outdoors/indoors, process conditions related to temperature and pressure. Technical conditions and measures at process level (source) to prevent release Process design aiming to prevent releases and hence exposure of workers; this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure		
Duration per task/activity (e.g. hours per shift) and frequency (e.g. single events or repeated) of exposure Human factors not influenced by risk management Particular conditions of use, e.g. body parts potentially exposed as a result of the nature of the activity Other given operational conditions affecting workers exposure Other given operational conditions: e.g. technology or process techniques determining the initial release of substance from process into workers environment; room volume, whether the work is carried out outdoors/indoors, process conditions related to temperature and pressure. Technical conditions and measures at process level (source) to prevent release Process design aiming to prevent releases and hence exposure of workers; this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure	Amounts used at a workplace (per task or per shift); note: sometime	es this Not applicable
events or repeated) of exposure Human factors not influenced by risk management Particular conditions of use, e.g. body parts potentially exposed as a result of the nature of the activity Other given operational conditions affecting workers exposure Other given operational conditions: e.g. technology or process techniques determining the initial release of substance from process into workers environment; room volume, whether the work is carried out outdoors/indoors, process conditions related to temperature and pressure. Technical conditions and measures at process level (source) to prevent release Process design aiming to prevent releases and hence exposure of workers; this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure	Frequency and duration of use/exposure	
Particular conditions of use, e.g. body parts potentially exposed as a result of the nature of the activity Other given operational conditions affecting workers exposure Other given operational conditions: e.g. technology or process techniques determining the initial release of substance from process into workers environment; room volume, whether the work is carried out outdoors/indoors, process conditions related to temperature and pressure. Technical conditions and measures at process level (source) to prevent release Process design aiming to prevent releases and hence exposure of workers; this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure	events or repeated) of exposure	single More than 4 hours per day
as a result of the nature of the activity Other given operational conditions affecting workers exposure Other given operational conditions: e.g. technology or process techniques determining the initial release of substance from process into workers environment; room volume, whether the work is carried out outdoors/indoors, process conditions related to temperature and pressure. Technical conditions and measures at process level (source) to prevent release Process design aiming to prevent releases and hence exposure of workers; this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure	Human factors not influenced by risk management	
Other given operational conditions affecting workers exposure Other given operational conditions: e.g. technology or process techniques determining the initial release of substance from process into workers environment; room volume, whether the work is carried out outdoors/indoors, process conditions related to temperature and pressure. Technical conditions and measures at process level (source) to prevent release Process design aiming to prevent releases and hence exposure of workers; this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure		Not applicable
Other given operational conditions: e.g. technology or process techniques determining the initial release of substance from process into workers environment; room volume, whether the work is carried out outdoors/indoors, process conditions related to temperature and pressure. Technical conditions and measures at process level (source) to prevent release Process design aiming to prevent releases and hence exposure of workers; this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure	as a result of the nature of the activity	
determining the initial release of substance from process into workers environment; room volume, whether the work is carried out outdoors/indoors, process conditions related to temperature and pressure. Technical conditions and measures at process level (source) to prevent release Process design aiming to prevent releases and hence exposure of workers; this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure	Other given operational conditions affecting workers exposure	
Technical conditions and measures at process level (source) to prevent release Process design aiming to prevent releases and hence exposure of workers; this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure	determining the initial release of substance from process into worke environment; room volume, whether the work is carried out outdoors/indoors, process conditions related to temperature and	
Process design aiming to prevent releases and hence exposure of workers; this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure		event release
this in particular includes conditions ensuring rigorous containment; performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure		
performance of containment to be specified (e.g. by quantification of residual losses or exposure) Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure		
Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure		
Technical conditions and measures to control dispersion from source towards the worker Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure Organisational measures to prevent /limit releases, dispersion and exposure		
Engineering controls, e.g. exhaust ventilation, general ventilation; specify effectiveness of measure 1. Containment as appropriate 2. Good standard of general ventilation Organisational measures to prevent /limit releases, dispersion and exposure	, ,	rce towards the worker
	Engineering controls, e.g. exhaust ventilation, general ventilation; sp	pecify 1. Containment as appropriate
Specific organisational measures or measures needed to support the Not applicable	Organisational measures to prevent /limit releases, dispersion and	d exposure
functioning of particular technical measures (e.g. training and supervision). Those measures need to be reported in particular for demonstrating	Specific organisational measures or measures needed to support the functioning of particular technical measures (e.g. training and super	e Not applicable rvision).

according to Regulation (EC) No. 453/2010



CalMag Zinc Horticultural Grade

strictly controlled conditions (to justify exposure based waiving).		
Conditions and measures related to personal protection, hygiene and hea	th evaluation	
Personal protection, e.g. wearing of gloves, face protection, full body dermal protection, goggles, respirator; specify effectiveness of measure; specify the suitable material for the PPE (where relevant) and advise how long the protective equipment can be used before replacement (if relevant)	1. PPE	
3 Exposure information and reference to its source		

Information for contributing scenario 1

An environmental assessment has not been performed as the substance does not meet the criteria for being classified as dangerous for the environment.

Information for contributing scenario 2

A qualitative approach was used to conclude safe use for workers.

The leading toxicological effect is eye irritation (local endpoint), for which no DNEL can be derived as no dose-response information is available. Although acute orally harmful, the acute oral route is not considered a relevant exposure route in the exposure scenarios described and no peak exposure is possible via this route. The substance did not show any systemic effects in the repeated dose studies and thus a quantitative assessment for systemic toxicity is not considered relevant for this substance.

4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

No additional risk management measures, besides those that are mentioned above, are needed to guarantee safe use for workers.

5 Additional good practice advice beyond the REACH CSA

Additional good practices (Operational Conditions and Risk Management Measures) beyond the REACH Chemical Safety Assessment established within Chemical Industry are also advised and communicated through Safety Data Sheets. Such as:

- Containment as appropriate;
- Minimise number of staff exposed;
- Segregation of the emitting process;
- Effective contaminant extraction;
 - Good standard of general ventilation;
- Minimisation of manual phases;
- Avoidance of contact with contaminated tools and objects;
- Regular cleaning of equipment and work area;
- Management/supervision in place to check that RMMs in place are being used correctly and OCs followed;
- Training staff on good practice;
- Good standard of personal hygiene;

Environmental release during manufacturing

Exposure scenario (2) For calcium nitrate		
Professional US	SE of substance as fertilizer	
Use descriptors related to the life cycle stage	SU: 0-1/1 PROC2/5/8a/8b/9/11/19 ER2 PC 12: Fertilisers	
Name of contributing environmental scenario (1) and corresponding ERC Professional USE of substance as fertilizer - solid at Farm - loading and spreading (includes soil conditioning) - solid in Greenhouse (e.g. Fertigation, pH control with acid) - as liquid fertilizer in open field (e.g. Fertigation) - maintenance of equipment		
List of names of contributing worker scenarios (2) and corresponding PROC PROC 2: Use in closed, continuous process with occasional controlled exposure PROC 8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non- dedicated facilities PROC 8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC 9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC 11: Non industrial spraying PROC 19: Hand-mixing with intimate contact and only PPE available		

according to Regulation (EC) No. 453/2010



CalMag Zinc Horticultural Grade

ERC 7	FDC 0-1Wide diaments and an use of marking substance in
ERC 8b: Wide dispersive indoor use of reactive substances in open systems	ERC 8e: Wide dispersive outdoor use of reactive substances in open
systems	
An environmental assessment has not been performed as the substance do	es not meet the criteria for being classified as dangerous for the
environment.	
2.2 Contributing scenario (2) controlling worker exposure for manufacturing	
All Process Categories are covered by this contributing scenario as all Opera	tional Conditions (OCs) and Risk Management
Measures (RMMs) are identical. PROC2/5/8a/8b/9	
Product characteristic	
Product related conditions, e.g. the concentration of the substance in a	Solid, very low dustiness
mixture, the physical state of that mixture (solid, liquid; if solid: level of	
dustiness), package design affecting exposure	
Amounts used	
Amounts used at a workplace (per task or per shift); note: sometimes this	Not applicable
information is not needed for assessment of worker's exposure	
Frequency and duration of use/exposure	
Duration per task/activity (e.g. hours per shift) and frequency (e.g. single	More than 4 hours per day
events or repeated) of exposure	more than 4 hours per day
Human factors not influenced by risk management	
Particular conditions of use, e.g. body parts potentially exposed as a result	Not applicable
	Not applicable
of the nature of the activity	
Other given operational conditions affecting workers exposure	T
Other given operational conditions: e.g. technology or process techniques	Indoors
determining the initial release of substance from process into workers	
environment; room volume, whether the work is carried out	
outdoors/indoors, process conditions related to temperature and	
pressure.	
Technical conditions and measures at process level (source) to prevent rel	ease
Process design aiming to prevent releases and hence exposure of workers;	Not applicable
this in particular includes conditions ensuring rigorous containment;	
performance of containment to be specified (e.g. by quantification of	
residual losses or exposure)	
Technical conditions and measures to control dispersion from source toward	ards the worker
Engineering controls, e.g. exhaust ventilation, general ventilation; specify	3. Containment as appropriate
effectiveness of measure	4. Good standard of general ventilation
Organisational measures to prevent /limit releases, dispersion and exposu	ire
Specific organisational measures or measures needed to support the	Not applicable
functioning of particular technical measures (e.g. training and supervision).	
Those measures need to be reported in particular for demonstrating	
strictly controlled conditions (to justify exposure based waiving).	
Conditions and measures related to personal protection, hygiene and heal	th evaluation
Personal protection, e.g. wearing of gloves, face protection, full body	2. PPE
dermal protection, goggles, respirator; specify effectiveness of measure;	
specify the suitable material for the PPE (where relevant) and advise how	
long the protective equipment can be used before replacement (if	
relevant)	
,	
3 Exposure information and reference to its source	
Information for contributing scenario 1	
An environmental assessment has not been performed as the substance do	es not meet the criteria for being classified as dangerous for the
environment.	

4 Guidance to DU to evaluate whether he works inside the boundaries set by the ES

quantitative assessment for systemic toxicity is not considered relevant for this substance.

A qualitative approach was used to conclude safe use for workers.

Information for contributing scenario 2

No additional risk management measures, besides those that are mentioned above, are needed to guarantee safe use for workers.

The leading toxicological effect is eye irritation (local endpoint), for which no DNEL can be derived as no dose-response information is available. Although acute orally harmful, the acute oral route is not considered a relevant exposure route in the exposure scenarios described and no peak exposure is possible via this route. The substance did not show any systemic effects in the repeated dose studies and thus a

according to Regulation (EC) No. 453/2010



CalMag Zinc Horticultural Grade

5 Additional good practice advice beyond the REACH CSA

Additional good practices (Operational Conditions and Risk Management Measures) beyond the REACH Chemical Safety Assessment established within Chemical Industry are also advised and communicated through Safety Data Sheets. Such as:

- Containment as appropriate;
- Minimise number of staff exposed;
- Segregation of the emitting process;
- Effective contaminant extraction;
- Good standard of general ventilation;
- Minimisation of manual phases;
- Avoidance of contact with contaminated tools and objects;
- Regular cleaning of equipment and work area;
- Management/supervision in place to check that RMMs in place are being used correctly and OCs followed;
- Training staff on good practice;
- Good standard of personal hygiene;